



- 1 Surface finish
SEDA | TENSEO X-MATT | PUROTEC
- 2 Wear layer of approx. 3.6 mm
from selected solid wood
- 3 Core layer of quarter sawn European
conifer wood
- 4 5G-interlocking system
- 5 Ends with hydrophobic impregnation,
prevents humidity and reduces creaking
of wood
- 6 2 mm spruce bottom
veneer sanded

PRODUCT	DIMENSIONS	PACKAGING	WEIGHT/PACK	PACKAGING	WEIGHT/PAL.
MULTIflor 2400.11 NOVOLOC® 5G	11 x 222 x 2400 mm	6 pieces/pack = 3.197 m ²	approx. 24 kg	40 packs/pallet = 127.9 m ²	approx. 940 kg
MULTIflor 2200.11 NOVOLOC® 5G	11 x 182 x 2200 mm	6 pieces/pack = 2.402 m ²	approx. 18 kg	50 packs/pallet = 120.1 m ²	approx. 890 kg
MULTIflor 1800.11 NOVOLOC® 5G	11 x 140 x 1800 mm	12 pieces/pack = 3.024 m ²	approx. 22 kg	42 packs/pallet = 127.0 m ²	approx. 930 kg
MULTIflor 1200.11 NOVOLOC® 5G	11 x 140 x 1200 mm	12 pieces/pack = 2.016 m ²	approx. 15 kg	42 packs/pallet = 84.7 m ²	approx. 620 kg

PRODUCT FEATURES	
Multilayer-parquet with NOVOLOC® 5G interlocking system for glue-down installation on standard-compliant subfloors, according to EN 13489:2021	
Wear layer	1-strip from selected solid wood with a wear layer of approx. 3.6 mm
Core layer	Central European conifer wood in spruce or pine with plywood end caps
Back layer	spruce veneer
Moisture content	delivered with a moisture content of 7 % +/- 2 %. according to EN 13489:2021
Gluing	RPU gluing, 100% formaldehyde-free, waterproof, heat-resistant
Surface	Naturally oiled, oxidative drying surface:
Further details on surface treatments can be found in the respective data sheets.	<p>SEDA Our oils/waxes are based on natural raw materials and dry purely by oxidation, are not film-forming and partially repairable.</p> <p>Varnished surfaces: UV-lacquers from Bona, Sweden: TENSEO CLASSICO (gloss level 29±5 °GU) TENSEO X-MATT with excimer technology (gloss level 9±2 °GU) PUROTEC with excimer technology (gloss level 5 ±1°GU)</p>
Installation	Glue-down installation with NOVOLOC® 5G interlocking system
Underfloor heating	suitable, R _T = 0.078 m ² K/W, please pay attention to our specifications for the installation above underfloor heatings
Fields of use	Floors and walls, living and object area (meet the highest class C according to ÖN C2354)
Room climate	Room temperature should be kept at a constant of 18–24°C and the relative humidity between 30% und 65%! This generally requires an appropriate air humidification in the heating season. We therefore recommend cold humidifiers with an integrated sterilization system. The installation of a Fidbox records your climate above and under your parquet floor, reports deviations from the optimum climate and can be conveniently monitored by mobile app.

Reaction to fire	C _{fl} - s1 ≥ 500 kg/m ³ 11 mm
Formaldehyde emission	E1
PCP emission	<5 × 10 ⁻⁶
Thermal conductivity	0.14 W/mK
Biological durability	Class 1
Release of other dangerous substances	complies with EU-ECOLABEL, German AgBB-scheme, French. A+, Belgian VOC Regulation, LEED v4, BREEAM Gen.Level

